



Rated starter currents:

Starter size	Rated current at temperatures up to +55°C, A	Thermal overload relay setting range
1	0,13	0,10 – 0,13
	0,17	0,13 – 0,17
	0,23	0,17 – 0,23
	0,31	0,23 – 0,31
	0,41	0,31 – 0,41
	0,55	0,41 – 0,55
	0,74	0,55 – 0,74
	1,00	0,74 – 1,00
	1,30	1,00 – 1,30
	1,70	1,30 – 1,70
	2,30	1,70 – 2,30
	3,10	2,30 – 3,10
	4,20	3,10 - 4,20
	5,70	4,20 - 5,70
	7,60	5,70 - 7,60
	10	7,60 - 10
	13	10 - 13
	16	13 - 16
2	20	16 - 20
	24	20 - 24
	29	24 - 29

Starter size	Rated current at temperatures up to +55°C, A	Thermal overload relay setting range
3	35	29 - 35
	38	35 - 38
	42	29 - 42
	52	36 – 52
	63	45 – 63
4	63	45 – 63
	80	60 – 80
	90	65 – 90
5	110	80 – 110
	135	100 – 135
	150	110 - 150
	175	130 – 175
	200	150 – 200
	235	165 – 235
	250	220 - 250

Junction boxes

Metal junction boxes

Plug transformers

Push-button stations

Cam switches

Cam selector switches

Cabin switches and sockets

Junction boxes with protection unit

Power boxes with protection unit

Interference suppression filters

Electromagnetic starters

AC UPS

DC UPS

Media server

Supply with acceptance:
 - RMRS
 - RRR
 - VP

