



Arus nominal starter:

Ukuran starter	Arus nominal pada suhu hingga +55°C, A	Rentang setelan relai beban lebih termal
1	0,13	0,10 – 0,13
	0,17	0,13 – 0,17
	0,23	0,17 – 0,23
	0,31	0,23 – 0,31
	0,41	0,31 – 0,41
	0,55	0,41 – 0,55
	0,74	0,55 – 0,74
	1,00	0,74 – 1,00
	1,30	1,00 – 1,30
	1,70	1,30 – 1,70
	2,30	1,70 – 2,30
	3,10	2,30 – 3,10
	4,20	3,10 - 4,20
	5,70	4,20 - 5,70
	7,60	5,70 - 7,60
	10	7,60 - 10
	13	10 - 13
	16	13 - 16
2	20	16 - 20
	24	20 - 24
	29	24 - 29

Ukuran starter	Arus nominal pada suhu hingga +55°C, A	Rentang setelan relai beban lebih termal
3	35	29 - 35
	38	35 - 38
	42	29 - 42
	52	36 – 52
	63	45 – 63
4	63	45 – 63
	80	60 – 80
	90	65 – 90
	110	80 – 110
5	135	100 – 135
	150	110 - 150
	175	130 – 175
	200	150 – 200
	235	165 – 235
	250	220 - 250

Pasokan dengan penerimaan:

- RMRS
- RRR
- VP

